

### Advantages

- Long life according to EUROBAT Classification
- High discharge performance
- 99%+ gas recombination efficiency
- Maximum charge efficiency
- Low self-discharge rate
- Easy installation and handling

### Application


- Telecommunication
- Power system
- UPS
- Emergency power

### Standards

- IEC 60896-21/22:2004
- JIS C8704-1/2:2006
- Eurobat guide
- installation compliant with EN50272-2



### Drawing



### Specification





Battery Model	GFM-2000C			
Designed Life(Years)	15			
Capacity(Ah/25°C)	10HR(200A, 1.80V)	5HR(340A, 1.80V)	3HR(500A, 1.80V)	1HR(1100A, 1.75V)
	2000	1700	1500	1100
Dimensions	Length(mm)	Width(mm)	Height(mm)	Total Height(mm)
	433	342	341	351
Approx.Weight(Kg)	118			
Internal Resistance(m $\Omega$ )	0.1			
Max. Discharge Current(A/5Sec.)	9000			
Self Discharge(25°C)	<=1% per month			
Charge Voltage(V/25°C)	Cycle use		Float use	
	2.35(-3.5mV/°C),max charge current:300A		2.25(-3.5mV/°C)	

## Discharge Data

Constant current discharge data(25°C,A)															
Endvoltage (V/cell)	5min	10min	15min	20min	30min	40min	50min	1h	1.5h	2h	3h	5h	8h	10h	24h
1.60	4200	3245	2685	2311	1834	1537	1331	1160	890	722	533	357	247	206	88.2
1.65	3818	2971	2481	2153	1731	1464	1277	1140	869	710	525	352	244	204	87.6
1.67	3689	2849	2388	2080	1681	1428	1250	1123	857	704	521	351	243	204	87.4
1.70	3486	2727	2295	2006	1631	1392	1223	1107	846	697	518	349	242	203	87.1
1.75	3050	2512	2161	1912	1576	1355	1195	1100	833	685	509	344	240	201	86.5
1.80	2677	2325	2040	1824	1517	1310	1158	1048	810	669	500	340	237	200	85.9

Constant power discharge data(25°C,W/Cell)															
Endvoltage (V/cell)	5min	10min	15min	20min	30min	40min	50min	1h	1.5h	2h	3h	5h	8h	10h	24h
1.60	6120	5261	4435	3926	3090	2590	2291	2040	1588	1312	974	660	475	396	177
1.65	5622	4776	4064	3621	2870	2440	2178	1970	1527	1267	948	648	469	389	175
1.67	5292	4576	3922	3504	2774	2376	2119	1942	1508	1250	938	644	466	388	173
1.70	4962	4376	3780	3386	2679	2313	2061	1913	1488	1233	928	639	463	386	172
1.75	4446	4046	3523	3148	2511	2173	1968	1823	1446	1202	909	628	457	381	170
1.80	4086	3713	3228	2900	2355	2053	1897	1741	1402	1169	891	617	451	377	167

## Performance Curve



**Sacred Sun Power Source Co.,Ltd.**

No.1 Shengyang Road, Qufu City, PRC  
 Website: www.sacredsun.com

**Sacred Sun Asia Pacific**

10Q,10thFloor, Xinbaohui Building, Nanhai Boulevard,  
 Nanshan, Shenzhen, PRC.

**Sacred Sun Europe SPRL**

Paul Dejaerlaan 4b, B 1060 Brussel, Belgium

